

STANDARD SPECIFICATIONS

10 YEAR WARRANTY

	THE CONTRACTOR OF THE CONTRACT					
Applications	Offices, Schools, Hospitals, Apartments, Hotel/Motels & other Public Buildings	Mounting	Furnished standard with wood & machine screws. Sex nuts and bolts (1346) optional.			
Door Thickness	1-3/4" ~ 2" standard, 2-1/4" optional	Latchbolt	Zinc with 3/4" throw.			
Door Size	33" to 36". Bar can be easily field cut to size.	Latchbolt Spring Stainless Steel throughout.				
Stile Width	4-1/2" minimum stile width required.	Guard Bolt	Stainless Steel			
Chasis, End Cap & Rail Assembly	Painted Steel (Alum & Duro) or Stainless Steel (US32D)	Strike	#8170 Steel Roller Strike 2-3/4" Backset. Optional Strike #8070 for 2-3/8" Baskset.			
UL Listed	Complies with UL 305 standards. Listed for safety as Panic Hardware.		4-7/8 Blank Strike & 161 Edge Filler			
		Cover	Zinc Alloy			
Rating	ANSI 156.3 Grade 1	Handing	Non Handed			
Door Prep	Will cover stock hollow metal doors with 161 cutout	Dogging	Hex Key Dogging feature standard			

ITEM DETAILS

Model	Description	WT/ CTN	QTY/ CTN		ALUMINUM	US32D Stainless Steel
9000-36	HD Rim Type Device for 36" Door	46 Lbs	4	Item No.	691300	691301
9000-36 AL	HD Rim Type Device for 36" Door with Alarm Kit "C" Cylinder	46 Lbs	4	Item No.	691300C	691301C
9000-36 AL	HD Rim Type Device for 36" Door with Alarm Kit "KW1" Cylinder	46 Lbs	4	Item No.	691300K	691301K



EXTERIOR OPTIONS

